In the Claims:

Please amend the claims as follows:

1.   (Currently Amended) A communication system for managing messages, comprising:

means for retrievably storing at least one message <u>on-board</u>;

means for retrieving said at least one message;

means for transmitting said at least one message to a user; and

at least one motion detector for detecting motion within a selected range of said communication system, wherein said means for retrievably storing said message, said means for retrieving said message and said means for transmitting said message to a user are in communication with said at least one motion detector, wherein said at least one motion detector transmits a signal upon detection of motion within said selected range of said communication system and activates said means for transmitting said at least one message, wherein upon activation, said means for transmitting said at least one message transmits a message status statement to the user, wherein said means for transmitting said at least one message requires a direct order to perform a task, said direct order selected from a group of orders

comprising play, erase, save, repeat, forward, reply, datestamp, playback, stop, and delete, wherein a voice control system receives, recognizes and interprets each said direct order from the user irrespective of the sequence, and directs a microprocessor in accordance with a task objective of each said direct order.

2.   (Cancelled)   A method of managing electronic messages, comprising the steps of:

    a.   retrievably storing a message;

    b.   detecting the presence of a user; and

    c.   transmitting said message to the user.

3.   (Original)   The communication system for managing messages of Claim 1, wherein said at least one motion detector is an infrared radiation detector.

4.   (Original)   The communication system for managing messages of Claim 1, wherein said at least one motion detector is an optical system.

5.   (Cancelled)   The communication system for managing messages of Claim 1, wherein said voice control system receives, recognizes and interprets a plurality of voice commands and directs said microprocessor in accordance with a control objective of each said voice command.

6.   (Previously Presented)   The communication system for managing messages of Claim 1, wherein said microprocessor utilizes a software programmed vocabulary to execute said task objective of each said direct order.

7.   (Currently Amended) The communication system for managing messages of Claim 1, wherein ~~said group of orders further comprises a direct order enabling~~ a message to be delivered to a user <u>may, at the direction of the message creator, be stored for retrieval</u> at a designated date.

8.   (Currently Amended) The communication system for managing messages of Claim 1, further comprising a timer apparatus, wherein operation of said at least one motion detector <u>may be prevented</u> ~~is limited to a specified interval of~~ <u>by</u> said timer apparatus.

9.   (Previously Presented)   The communication system for managing messages of Claim 1, wherein said means for retrievably storing at least one message is a recording unit, said recording unit enabling receipt, storage and playback of a plurality of messages;

and wherein said means for retrieving said at least one message and said means for transmitting said at least one message to a user comprise said microprocessor, wherein said microprocessor receives said direct orders from a voice control system, said voice control

system having a microphone and said voice control system enabling the user to verbally command said microprocessor; a speaker, wherein said speaker is activated by said microprocessor in response to said signal from said at least one motion detector, wherein said speaker audibly announces information regarding status and operation of said recording unit, and wherein said speaker is responsive to said microprocessor via said voice control system and audibly communicates each message of said plurality of messages received and stored by said recording unit and selected for playback; and a message monitoring means.

10. (Original)   The communication system for managing messages of Claim 9, wherein said message monitoring means is an event counter, wherein said event counter increases by an incremental unit for each said message of said plurality of messages received and stored by said recording unit, and wherein said event counter decreases by said incremental unit for each said message of said plurality of messages deleted from said plurality of messages received and stored by said recording unit.

11. (Original)   The communication system for managing messages of Claim 10, wherein said voice control system, said recording unit, said microprocessor, said speaker and said event counter are carried within a housing unit.

6

12. (Original) The communication system for managing messages of Claim 9, wherein said recording unit receives each said message of said plurality of messages at least from incoming telephone messages.

13. (Original) The communication system for managing messages of Claim 9, wherein said recording unit receives each said message of said plurality of messages at least from said microphone.

14. (Original) The communication system for managing messages of Claim 1, wherein said means for retrieving said message and said means for transmitting said message to a user comprise a microprocessor, wherein said microprocessor receives said signal from said at least one motion detector, wherein said microprocessor includes communication software for controlling communications in a telephone system, and wherein said microprocessor receives commands from a voice control system, said voice control system having a microphone and said voice control system enabling a user to verbally command said microprocessor; a speaker, wherein said speaker is activated by said microprocessor in response to said signal from said at least one motion detector, wherein said speaker audibly announces information regarding status and operation of a voice mail system, and wherein said speaker is responsive to said microprocessor via said voice control system and audibly communicates each message of said plurality of messages received and stored by the voice mail

7

system; and a message monitoring means, wherein said message monitoring means responds to an audible indicator of the voice mail system to indicate the presence of at least one message received and stored by the voice mail system, and

wherein said means for retrievably storing a message is a voice mail systems interface, said voice mail systems interface enabling said microprocessor to utilize an external telephone line to access and operate the voice mail system.

15. (Original)   The communication system for managing messages of Claim 14, wherein said microprocessor converts said commands received from said voice control system into corresponding tone frequencies of a telephone keypad.

16. (Original)   The communication system for managing messages of Claim 1, wherein said means for retrieving said message and said means for transmitting said message to a user comprise a microprocessor, wherein said microprocessor receives said signal from said at least one motion detector and wherein said microprocessor receives commands from a voice control system, said voice control system having a microphone and said voice control system enabling a user to verbally command said microprocessor; a speaker, wherein said speaker is activated by said microprocessor in response to said signal from said at least one motion detector, wherein said speaker audibly announces information regarding status and operation of an

electronic mail system, and wherein said speaker is responsive to said microprocessor via said voice control system and audibly communicates each message of said plurality of messages received and stored by the electronic mail system; and a message monitoring means, wherein said message monitoring means responds to an indicator of the electronic mail system to indicate the presence of at least one message received and stored by the electronic mail system, and

wherein said means for retrievably storing a message is a computer unit interface, said computer unit interface enabling said microprocessor to access and operate the electronic mail system.

17. (Original) The communication system for managing messages of Claim 16, wherein said microprocessor includes software enabling said microprocessor to direct the electronic mail system via said computer unit interface, wherein said verbal commands from said voice control system are utilized for operative control of a computer unit.

18. (Original) The communication system for managing messages of Claim 17, wherein said verbal commands from said voice control system are substituted for manipulation of a pointing device for control of motion of a cursor on a computer display and are utilized for operative control of the computer unit.

19. (Original). The communication system for managing messages of Claim 16, further comprising an audible reminder, wherein said audible reminder is programmable for delivery at a specified time.

20. (Cancelled) A communication system for managing electronic messages, comprising:

at least one motion detector, wherein said at least one motion detector transmits a signal upon detection of motion within a selected range of said communication system,

a microprocessor, wherein said microprocessor receives said signal from said at least one motion detector, wherein said microprocessor includes software enabling said microprocessor to direct the electronic mail system via a computer interface unit, wherein said verbal commands from a voice control system are utilized for operative control of a computer unit, and wherein said microprocessor receives commands from said voice control system and utilizes a software programmed vocabulary to execute a control objective of each said command;

a voice control system, said voice control system having a microphone, said voice control system enabling a user to verbally command said microprocessor; and wherein said voice control system receives, recognizes and interprets a plurality of voice commands and directs said microprocessor in accordance with a control objective of each said voice command;

10

a speaker, wherein said speaker is activated by said microprocessor in response to said signal from said at least one motion detector, wherein said speaker audibly announces information regarding status and operation of an electronic mail system, and wherein said speaker is responsive to said microprocessor via said voice control system and audibly communicates each message of said plurality of messages received and stored by the electronic mail system;

a message monitoring means, wherein said message monitoring means responds to an indicator of the electronic mail system to indicate the presence of at least one message received and stored by the electronic mail system;

a computer interface unit, said computer interface unit enabling said microprocessor to access and operate the electronic mail system;

an audible reminder, wherein said audible reminder is programmable for delivery at a specified time; and

a timer apparatus, wherein operation of said at least one motion detector may be selectively limited to at least one specified interval of said timer apparatus.

21. (Previously Presented) A method of managing electronic messages, comprising the steps of:

a. obtaining a portable, dedicated communication system for managing messages, comprising means for retrievably storing at

least one message; means for retrieving said at least one message; means for transmitting said at least one message to a user; and at least one motion detector for detecting motion within a selected range of said communication system, wherein said means for retrievably storing said message, said means for retrieving said message and said means for transmitting said message to a user are in communication with said at least one motion detector, and wherein said at least one motion detector transmits a signal upon detection of motion within said selected range of said communication system and activates said means for transmitting said at least one message;

       b.   selecting a location for placement of said communication system;

       c.   retrievably storing a message;

       d.   detecting the presence of a user via said motion detector;

       e.   notifying the user of message status; and

       f.   allowing the user to verbally dictate from set of commands to direct subsequent message handling.

    22.   (Currently Amended) A communication system for managing messages, comprising:

    a <u>plurality of</u> message storage ~~device~~ means, said <u>plurality of message storage means comprising a telephone answering machine, an electronic voicemail system, and an electronic text mail system, wherein said electronic text mail system further comprises telephonic</u>

12

text messages and electronic mail transmitted via a global networking system;

a microprocessor, integrated with said telephone answering machine, for retrieving the stored messages and transmitting the stored messages to a user via verbal signals emanating from said telephone answering machine, said microprocessor adapted to receive a user-selected audible verb-form directive from the user, via a microphone in said telephone answering machine, and to perform a message-related task as directed by said verb, said message-related tasks comprising operational controls for said telephone answering machine, said electronic voicemail system and said electronic text mail system; and

a motion detector for detecting motion within a selected range of said telephone answering machine communication system,

wherein said microprocessor and said plurality of message storage device means, via said microprocessor, are in communication with said motion detector,

wherein said motion detector transmits a signal to said microprocessor upon detection of motion,

wherein said signaled microprocessor transmits a status of said plurality of message storage device means statement to the user, via a verbal announcement from said telephone answering machine,

wherein the user articulates a task to be performed by the said microprocessor via an audible verb-form directive, whereby the user dictates the order and the function of said tasks performed by said

microprocessor <u>and by each said message storage means</u>.